



OP medical print®

OP medical print® has the exclusive combination of extra high printed opacity with a pleasant whiteness for best readability. The unique surface properties reduce the ink consumption and deliver an unmatched high printed opacity even in multi-colored printing on low substances. State-of-the-art production technology ensures excellent folding properties at very low substances and makes OP medical print® the first choice for complex folding jobs.

applications

- pharma and cosmetic leaflets
- technical manuals



specifications

parameter	unit							standard
substance	gsm	32.0	35.0	40.0	45.0	50.0	60.0	ISO 536
basis weight	lbs	21.5	23.5	27.0	30.5	34.0	40.5	25"x38"/500
caliper	µm	40.0	44.0	50.0	56.0	62.5	75.0	ISO 534
UV brightness (D65)	%	95.0	95.0	95.0	95.0	95.0	95.0	ISO 2470-2
CIE whiteness		115.0	115.0	115.0	115.0	115.0	115.0	ISO 11475
opacity	%	81.0	83.0	84.0	86.0	88.0	91.0	ISO 2471
roughness	ml/min	<300	<300	<300	<300	<300	<300	ISO 8791-2
luminescence		9.0	9.0	9.0	9.0	9.0	9.0	Laetus

Testing conditions: 50% r.h., 23°C

Reels

Width 250-2100 mm
DIA 1000-1500 mm

Sheets

317 mm x 430 mm LG
1250 mm x 1480 mm LG

Offset Printing

Web and sheet-fed
Coldset, heatset, UV-Offset

High Speed Inkjet

Canon Colorstream/Jetstream
(pigmented ink)/Prostream
Domino K630i
HP PageWide T-series/Advantage 2200
Ricoh V20100/VC20100/VC40000/
VC60000/VC70000/VC80000
Screen Truepress Jet520 NX/S/EX/ZZ/HD/HD+
Xerox Trivor HD/HF

Certificates

Quality ISO 9001
Environment ISO 14001
Food safety ISO 22000
Energy ISO 50001
Health & Safety ISO 45001
Chain of custody FSC™ (FSC-C111390)
Chain of custody PEFC (PEFC/08-33-0002)