flexible packaging food

delfort

thintwist®

high performance twisting paper

benefits

- significantly reduced wax costs due to lower wax consumption
- high opacity after waxing
- brilliant printing results for rotogravure and flexo
- excellent twisting and folding effects
- yield saving
- outstanding mechanical strength
- excellent haptic
- high runnability on converting machines
- recyclable according to Aticelca® 501 (in areas where recycling facilities and collecting are available)

available with optional features

- basis weight range from 30 to 45 g/m² (18.5 to 27.5 lbs)
- matt (coat)/glossy surface (gloss)
- without/with heat-sealing (HS)

applications

- base paper for waxing
- confectionary and candies
- bread wrapping
- various dry food and non-food packaging
- heat-sealable applications e.g. for bags, pouches, sachets, flow wrapping

variants

- thintwist®
- thintwist® coat
- thintwist® gloss
- thinseal

delfortgroup AG
food@delfortgroup.com / **www.delfortgroup.com**

flexible packaging food

delfort

thinbase® lamination / thinwrap™ fit

benefits

- base paper for converting
- suitable for AL and/or PE lamination
- significant glue savings due to high-density
- excellent converting and runnability
- flexo printability
- thinbarrier® eco M-2S-WS is recyclable according to Aticelca® 501 (in areas where recycling facilities and collecting are available)

features

- basis weight range from 22 to 49 g/m² (13.5 to 30 lbs)
- high strength and uniform formation
- thinbarrier® eco M-2S-WS (maximum grammage 38 g/m²) is certified OK compost HOME and OK compost INDUSTRIAL by TÜV Austria

applications

- base paper for printing, lamination
- confectionary wrapping
- thinbarrier® eco M-2S-WS to be suitable for butter wrapping

delfortgroup AG
food@delfortgroup.com / **www.delfortgroup.com**

flexible packaging food

delfort

thinbase® coat

multi-purpose high gloss coated paper

benefits

- suitable for AL and/or PE lamination, vacuum metallizing and waxing
- flexo and rotogravure printing
- 1-side clay coated paper for superior surface smoothness
- significant wax/glue savings due to high-density
- outperforming converting runnability

features

- basis weight range from 40 to 60 g/m² (24.5 to 37 lbs)
- 1-side coated high glossy paper
- high mechanical strength and uniform formation

applications

- base paper for converting
- dry food, pharmaceutical packaging
- food pouches, sachets, graphical applications

delfortgroup AG
food@delfortgroup.com / **www.delfortgroup.com**